



manufactured for Norton by



Pentra-Guard® (HP/S)

# Protector® (NON-POROUS)

## Advanced High-Gloss, Stain and Wear Protection Finish

### For Non-Porous, Highly Polished Surfaces

Concrete, Finished Stone & Terrazzo  
(1500 grit profiles and above)

#### MANUFACTURED BY

Convergent Concrete Technologies, LLC.  
Specialty Chemical Concrete Treatments  
450 South 1325 West Orem, Utah 84058  
Office: 801-375-2280 • Fax: 801-375-2971  
[www.convergentconcrete.com](http://www.convergentconcrete.com)

#### DISTRIBUTED BY

Saint-Gobain Abrasives, Inc.  
Worcester, MA 01606  
Imported by / Importé par  
Saint-Gobain Abrasives Canada Inc.  
Hamilton, ON L8L 7Y5  
[www.nortonconstructionproducts.com](http://www.nortonconstructionproducts.com)

#### TECHNICAL SERVICE

(254) 918-2310



extraordinarily friendly



lithium treatments

Go Green

## Great for Protecting Newly Polished Concrete, Factory-Finished Stone and Terrazzo Surfaces

#### ADVANTAGES

- Non-streaking, fast-curing protective treatment
- Leaves a durable, reflective surface
- Imparts high-gloss reflectivity when burnished
- Superior clarity, will not peel, flake or fade
- Easy to maintain and re-apply — chemically bonds
- Creates a tough wear surface.
- Heavy-duty protection against stains
- Easy-to-use, water-based formula
- VOC compliant, environmentally friendly
- Interior use only

#### DESCRIPTION

This patented lithium fortified finish offers deep penetration, increased surface hardness and superior reflectivity.

Apply with a microfiber pad and applicator then burnish with diamond-impregnated pads at high-speed (1500-2500 rpms). The result will be an immediate extremely glossy with excellent wear properties and extended life. The reactive micro-impregnating Nano Lithium™ polymer creates greater protection and greater gloss with less labor. Treated surfaces will have increased durability and abrasion resistance. We recommend two coats for initial protection. A retreatment every one to two years with Restorer® (CHEMICAL POLISH) will renew dulled surfaces. Maintenance with Refurbisher® (Mop 'N Buff) will help maintain reflectivity as well as preserve the polished finish. The unique treatment is extremely low in VOC's (less



manufactured for Norton by



than 50 grams per liter) and environmentally friendly. This product meets CSMA floor polish slip resistance requirements employing ASTM test method # D 2047.

#### PACKAGING SIZES AVAILABLE

1 Gallon Container, 5 Gallon Pail, 55 Gallon Drum & 275 Gallon Tote.

#### TYPICAL COVERAGE RATES

2000-3000 sq. ft. per gallon (60-90 m<sup>2</sup> per liter)

High Reflectivity 1500 + Grit profiles (2500 sq. ft. first application / 3000 sq. ft. second application).

#### GENERAL DIRECTIONS

Burnishing will revive the high-gloss and wear protection properties of the treated surface. Scuffing, heel and/or tire marks are easily burnished away after initial treatment.

#### APPLICATION INSTRUCTIONS

1. Deep scrub the floor with a ceramic black pad.
2. Mix, shake or stir thoroughly before applying
3. Choose from 12 - 24" microfiber application pads. Pad selection based on;
  - Size of application area.
  - Applicator's relative comfort level with application system.
4. Apply Protector® (NON-POROUS) Advanced High-Gloss, Stain and Wear Protection Finish using a clean, pre-dampened microfiber pad and applicator. Apply at a rate of 2500 - 3,000 sq. ft. per gallon depending on the surface profile spreading material thinly and evenly so as to completely cover the substrate. We recommend coating no larger than 20 x 20' sections at a time.
5. Allow to dry for 10-15 minutes. (Burnish / buff coating within 10-15 minutes of when it's dry.)
6. Burnish / buff with high-speed machine (1500-2500 rpms) using a fine / ultrafine diamond-impregnated pad. Burnishing of individual Protector® coats is highly recommended to improve curing process and overall shine. **IMPORTANT:** If floor is not burnished, allow each application to dry at least 30-60 minutes before reapplying next coat. Buffing between applications with a high-speed-burnisher accompanied by a diamond-impregnated pad system is the recommended method.

7. Repeat steps 4 & 5 depending on the surface profile and desired gloss levels. Repeated applications build a stain resistant microfilm over the substrate. Do not over apply. It is critical to apply very thin multiple coats. If applied too thickly it will cure improperly and discolor, whiten or leave streaks and/or applicator marks.
8. Do not to clean or scrub the surface for at least 72 hours. Clean up any accidental spills immediately.
9. **IMPORTANT:** Avoid moisture for 72 Hours. Do not allow standing water for 14 days. Do not place protective plastic sheeting, rubber matting, rugs or furniture that can prevent proper drying. Covering the surface can retard curing and result in a cloudy or whitening effect.
  - a. Light pedestrian use within 30 - 60 minutes, vehicle traffic in 2 hours.
  - b. Maximum performance may take up to 14 days to develop, depending on temperature and humidity.
  - c. Finish will reflect images from side and overhead lighting. The high-gloss finish will look wet and show mirror-like reflections of side and overhead images.

#### PROTECTION

- A. Do not allow standing water or puddles of water to be left on the surface. (Immediately wipe up any spills and/or water.)
- B. Do not to clean or scrub the surface for 72 hours (no moisture contact) to prevent the possibility of "whitening" or discoloration.
- C. Do not use protective sheeting (plastic) or other barrier sheeting to protect the surface from construction debris while the coating is curing.

#### CLEAN UP

Use water to clean tools and equipment. Treatments is environmentally friendly and requires no special or hazardous disposal methods.

#### MAINTENANCE

Routine sweeping, mopping, washing and mechanical scrubbing of floors with neutral pH cleaners/water is recommended. DO NOT USE acidic, citrus or butoxy-ethanol-containing cleaners to maintain the floor.



manufactured for Norton by



### PROFESSIONAL USE ONLY

Building Service Cleaning Professionals and Industrial Flooring Contractors. Not for sale to or resale to the general public. For authorized and trained applicators use only and must be applied by trained or certified contractors and / or licensed field service specialists.

### MANUFACTURED BY

Convergent Concrete Technologies, LLC.  
Specialty Chemical Concrete Treatments  
Commercial Products Group  
450 South 1325 West Orem, Utah 84058 • USA  
Office: 801-375-2280 • Fax: 801-375-2971  
[www.convergentconcrete.com](http://www.convergentconcrete.com)

### DISTRIBUTED BY

Saint-Gobain Abrasives, Inc.  
Worcester, MA 01606  
[www.nortonconstructionproducts.com](http://www.nortonconstructionproducts.com)

### TECHNICAL SERVICE

(254) 918-2310

### HEALTH AND SAFETY PRECAUTIONS

Protector® (NON-POROUS) Advanced High-Gloss, Stain and Wear Protection Finish is an aqueous Lithium silicate solution that uses proprietary compounds. The treatment is alkaline and may cause eye and skin irritation. KEEP OUT OF THE REACH OF CHILDREN. Do not take internally. Avoid prolonged contact with skin. Avoid ingestion of material. If swallowed, do not induce vomiting – call physician. Avoid contact with eyes. Protective clothing is recommended. Protective goggles are recommended in case of splashing. If splashed in eyes, wash immediately with clean water and call physician if irritation persists. Contact areas should be thoroughly washed with soap and water. Additional precautions, safety information and first aid treatments are contained in the Material Safety Data Sheet. Protector® (NON-POROUS) will bond to most surfaces - immediately wash off over spray with water and mild detergent. CAUTION: Surfaces wet with Protector® (NON-POROUS) may be slippery.

### FOR MEDICAL EMERGENCIES ONLY

Call Infotrac (800) 535-5053 Outside USA (352) 323-3500

### WARRANTY

LIMITED WARRANTY NOTICE Every reasonable effort is made to apply Convergent Concrete Technologies, LLC. exacting standards both in the manufacture of our products and in the information that we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, Convergent Concrete Technologies MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, and Convergent Concrete Technologies shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the Convergent Concrete Technologies Research Director. This information and all further technical advice are based on Convergent Concrete Technologies' present knowledge and experience. However, Convergent Concrete Technologies assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, Convergent Concrete Technologies disclaims all WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. CONVERGENT CONCRETE TECHNOLOGIES SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. Convergent Concrete Technologies reserves the right to make any changes according to technological progress or further developments. It is the customer's (Authorized Applicator) responsibility and obligation to carefully inspect and test any incoming goods. Performance of the products) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.

DISTRIBUTED BY  
Saint-Gobain Abrasives, Inc.  
Worcester, MA 01606

Imported by / Importé par  
Saint-Gobain Abrasives Canada Inc.  
Hamilton, ON L8L 7Y5

TECHNICAL SERVICE  
(254) 918-2310

WEB  
[www.nortonconstructionproducts.com](http://www.nortonconstructionproducts.com)